



PRODUCT DATA SHEET

Product: **BD-2 Medium Strength Paper Tape**

Description: A flatback, paper, pressure-sensitive tape featuring medium tensile strength with good edge tear resistance and excellent mass to mass adhesion.
Not recommended for high-temperature applications.

Nominal Values:

Backing	Flatback Kraft Paper
Adhesive	Synthetic Rubber / Resin
Adhesion to Steel (oz/in of width)	44 (12 N/25mm)
Tensile Strength (lbs/in of width)	32.5 (142 N/25mm)
Elongation (% at break)	3.5
Thickness (mils)	6.0 (0.152mm)
Mass to Mass Adhesion (oz/in of width)	123
Colors	White, Blue, Red

Product Application: Product is recommended for bandoliering (axial taping) electronic components, tape reeling and sequencing electronic components.

Standard Sizes: Spool - 6mm x 1000 yd. (914.4m), 2000 yd. (1828.8m),
3520 yd. (3218m) and 5000 yd. (4572m)
Pancake – 6mm (0.236”) x 180 yard (164.6m).

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

04/05