



PRODUCT DATA SHEET

Product: FM-71 Fineline Masking Tape

Description: FM-71 'fine line' masking tape uses thermally stabilized PVC backing with a rubber-based pressure-sensitive adhesive. This tape is designed to offer a high degree of conformability without excessive stretch. FM-71 will hold and cleanly remove from surfaces in the presence of 250°F (120°C) temperatures for at least 30 minutes. FM-71 assures the user of a secure lay-down, no residue on de-mask and a sharp / clean separation line.

Nominal Values:	Backing	Blue P.V.C.
	Adhesive	Natural Rubber
	Adhesion to Steel (oz/in of width)	20 (5.5 N/25mm)
	Tensile Strength (lbs/in of width)	14 (61.3 N/25mm)
	Elongation (% at break)	150
	Thickness (mils)	5.4 (0.137mm)

Product Application: Preferred for medium to high temperature applications where a sharp, fine line is required. FM-71 is used where a tape must meet a variety of paint masking applications.

Available Sizes: 1/8", 1/4", and 1/2" x 36 yards.
(3.17mm, 6.35mm and 12.7mm x 32.9m)

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

11/04