



intertape polymer group

#4379

Product Code **Poly Mask**

PRODUCT DATA SHEET

Product: #4379 Contractor Grade Poly-Masking Tape

Description: Poly-Mask tape is based on durable, moisture resistant PE (polyethylene) backing with a rubber-based pressure-sensitive adhesive that bonds well to most surfaces. This tape is designed to offer a high degree of conformability without excessive stretch. Easy Tear edges for ease of application. UV resistant and performs well over a wide range of temperature (including cold) conditions.

Nominal Values:	Backing	PE
	Color	Red
	Adhesive	Natural Rubber
	Adhesion to Steel (oz/in of width)	60 (16 N/25mm)
	Tensile Strength (lbs/in of width)	24 (105 N/25mm)
	Elongation (% at break)	70
	Thickness (mils)	7.5 (0.191mm)

Product Application: Preferred for use in Exterior Insulation and Finish Systems (EIFS) and as masking during stucco application. Can also be used for splicing PE films and surface protection.

Available Sizes: 2" x 60 yards

NOTICE: While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must by test or otherwise determine suitability for his purpose. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, Our standard terms and conditions of sale apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE IS EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

08/04