

123

MACHINE CUT STENCIL

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

High quality / durable stencil construction coated with an advanced rubber based medium tack pressure sensitive adhesive protected by a Light Blue poly liner. Designed for precision die cutting in Roller and Press machines. Unique rubber formula allows easy cutting with less wear on dies. The specially treated polyester liner maintains design alignment following plastic die removal. #123 is recommended for single-process shaped carving of marble and granite.

PRODUCT APPLICATIONS

For optimum performance, use with #223 or #333 Stencil Fillers.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Adhesive	Medium Tack / Rubber
Total Thickness (mil) PSTC-133	48 (1.22 mm)
Tensile Strength (lbs/in) PSTC-131	7 (30.6 N/25mm)
180° Adhesion to Steel (oz/in) PSTC-101	25 (6.8 N/25mm)
Elongation (% @ break) PSTC-131	450



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11

