

128 STENCIL

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

Hand cut / high quality / conformable / durable stencil coated with an advanced medium tack rubber based pressure-sensitive adhesive protected by an easy release White kraft paper liner. Thin 18 mil thick rubber was developed for sandblast glass etching. Also used for "skin-letter" frosting of polished granite. Unique rubber adhesive formula provides secure bond yet allows for easy / clean removal. Release treated paper liner allows easy design weeding and application. #128 is a proven product in the automotive and aeronautics industries for fine detail paint stripping applications.

PRODUCT APPLICATION

For sandblast glass etching and fine detail paint stripping.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Adhesive	Medium tack / Rubber
Total Thickness (mil) PSTC-133	24 (0.61 mm)
Tensile Strength (lbs/in) PSTC-131	4 (17.5 N/25mm)
180° Adhesion to Steel (oz/in) PSTC-101	18 (4.9 N/25mm)
Elongation (% @ break) PSTC-131	150



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11