

158

COMPUTER STENCIL

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

High quality / durable rubber coated stencil with a medium tack rubber adhesive rubber based pressure-sensitive adhesive protected by a Clear polyester liner. 1/2" on center hole pattern designed for IBM sprocket cutters. Tractor-feed holes are punched through liner and rubber. Designed and recommended for primed / painted hardwood, HDU foamboard, and polished surfaces. #158 provides a 25" width for #157 customers.

PRODUCT APPLICATIONS

#158 does not have inner polyester sheet. Therefore design centers must be taped before transferring stencil from plotter to surface. Can be used with #211 or #333 Stencil filler.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Adhesive	Medium Tack / Rubber
Total Thickness (mil) PSTC-133	46 (1.17 mm)
Tensile Strength (lbs/in) PSTC-131	7 (30.6 N/25mm)
180° Adhesion to Steel (oz/in) PSTC-101	23 (6.3 N/25mm)
Elongation (% @ break) PSTC-131	450



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11

