

192Y

COMPUTER STENCIL

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

High quality / durable stencil coated with an advanced medium tack rubber based pressure-sensitive adhesive protected by a Clear PET liner. Designed for precision cutting in IBM-pattern cutters. The slot-hole pattern will also accurately track through Gerber 15" and friction-feed plotters. #192Y contains an inner sheet of polyester which retains cut designs during liner removal. This same construction is found in #123, #124, and #154 Stencil products. Recommended for single process sandblast carving of granite or marble.

PRODUCT APPLICATIONS

For optimum performance, use with #223 or #333 Stencil Fillers. The 30" will work on large pin computer cutters. Replaces #123 in IBM plotter applications.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Adhesive	Medium Tack / Rubber
Total Thickness (mil) PSTC-133	49 (1.24 mm)
Tensile Strength (lbs/in) PSTC-131	6 (26.3 N/25mm)
180° Adhesion to Steel (oz/in) PSTC-101	19 (5.2 N/25mm)
Elongation (% @ break) PSTC-131	450



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11