

600PVC

2.3 MIL PVC SPECIALTY NATURAL RUBBER CST

DESCRIPTION

Chemical resistant, low stretch, UPVC (unplasticized polyvinyl chloride) film, coated with high quality, pressure-sensitive solvent natural rubber adhesive for consistent closure of corrugated and linerboard boxes.

With the most aggressive pressure-sensitive adhesive available, Central[®] Natural Rubber Tapes offer fast, positive bonding on “problem” applications such as high recycled content cartons, rough or ultra-smooth cartons, heavy ink coverage, dusty and/or dirty environments, humid conditions and temperature extremes.

PRODUCT APPLICATION

Bag sealing and color code identification. Light to medium duty box sealing and other packaging applications, and those exposed to rougher or more challenging shipping hazards and stress.



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 09/2010

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. This data should not be considered specification.

Backing (UPVC film)	1.4 mils (0.037 mm)
Adhesive	Solvent Natural Rubber
Tensile Strength ASTM D-3759	24 lbs/in width (420 N/100 mm)
Elongation (at break) ASTM D-3759	80%
Adhesion to Steel ASTM D-3330	20 oz/in (22 N/100 mm)
Shear to Linerboard (1/2"x1/2"x1000 grams) ASTM D-3654	2200+ minutes
Total Thickness ASTM D-3652	2.3 mils (.058 mm)
Application Range	32°F to 120°F (0°C ~ +49°C)
Operating Range	-30°F ~ +200°F (-35°C ~ +93°C)
Colors	Red, Orange, Yellow, Green, Light Blue, Dark Blue



CENTRAL
brand