

DCFA16B

1/16" UTILITY DOUBLE-COATED PE FOAM TAPE

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

DESCRIPTION

Black, cross-linked high density polyethylene, closed cell foam coated on both sides (double-coated) with a permanent bonding pressure-sensitive acrylic adhesive protected by an easy release treated 60# glassine (white) paper liner. Adhesion allows permanent bond to a variety of surfaces for mounting applications.

PRODUCT APPLICATION

Long term bonding. UV and chemical resistant. Mounting mirror and decorative tile, nameplate/emblem mounting, cushioning, dampening sound or vibration, gasketing, sealing against moisture, dust, and light, bonding wire harness clips, window glazing, adhering vinyl and plastic trim, molded plastics, and any application that requires the joining of two surfaces.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Closed cell / Cross-linked PE foam
Color	Black
Adhesive	Acrylic
Adhesion to Steel (oz/in of width)	55 (15 N/25mm)
Density (PFC)	4.0
Elongation (% at break)	11
Total Thickness w/o liner (inch)	1/16" (1.6 mm)
Shear Adhesion (hours) 1 kg / inch ²	>100
Service Temperature (Long term)	-4°F ~ +176°F (-20°C ~ +80°C)



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 06/09

