

DCP053A

MEDIUM GRADE DOUBLE-COATED ACRYLIC POLYESTER TAPE

DESCRIPTION

Polyester (PET) film coated on both sides with an aggressive pressure-sensitive acrylic adhesive. Excellent adhesion properties and good resistance to ultra-violet (UV) rays. Very good initial tack allowing immediate, permanent bond to a variety of surfaces. Features an easy release treated, HDPE coated 60# bleached kraft paper. Operating temperature range: 0° F to 150°F (-17°C to +65°C). Product is not repulpable.

PRODUCT APPLICATION

Photograph (clear mounting), nameplate mounting, assembling outdoor displays, splicing corrugated and paper, mounting plastic trim, bonding shrink film window insulation, and any application that requires the joining of two surfaces.



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	0.5 mil PET film
Adhesive	Solvent Acrylic
Adhesion to Steel (oz/in of width) PSTC-101	60 (16 N/25mm) face side 55 (15 N/25mm) liner side
Quick Stick to Steel (oz/in of width) PSTC-5	20 (5.5 N/25mm) face side 29 (7.9 N/25mm) liner side
Tensile Strength (lbs/in of width) PSTC-31	16 (70 N/25mm)
Elongation (at break) PSTC-31	125%
Total Thickness w/ liner (mils)	8.4 (0.21 mm)
Total Thickness w/o liner (mils) PSTC-33	3.9 (0.10 mm)
Liner Type / Thickness (mils) PSTC-33	PCK – White 4.5 (0.11 mm)
Color	Clear

