

RG22

263# PET SPECIALTY FILAMENT TAPE

DESCRIPTION

A clear, glass reinforced, polyester backed strapping tape with pressure-sensitive natural rubber/resin adhesive. High tensile strength, high adhesion and medium impact strength. Stain resistant and will not impart an odor or taste.

PRODUCT APPLICATION

Used in the appliance and furniture industries for securing components where direct contact with and subsequent removal from the surface of appliances is a factor. Product further provides safe, secure holding power to a variety of surfaces for packaging, bundling and palletizing applications.

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Polyester Film
Adhesive	Natural Rubber / Resin
Reinforcement	Fiberglass
Adhesion to Steel (oz/in of width) (at 90 degrees peel angle)	43 (11.7 N/25mm)
Tensile Strength (lbs/in of width)	263 (1150 N/25mm)
Elongation (at break)	4.3%
Total Thickness (mils)	7.0 (0.178 mm)
Quick Stick (oz/in of width)	
To Kraft	6 (1.6 N/25mm)
To Steel	27 (7.4 N/25mm)



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.



EFFECTIVE: 05/11