

RG9

131# PET MEDIUM GRADE FILAMENT TAPE

DESCRIPTION

A cold temperature, unidirectional fiberglass reinforced polyester backed strapping tape with natural rubber adhesive. Specially formulated natural color adhesive is designed for increased adhesion performance to many surfaces during exposure to cold temperatures. As ambient temperature rises, adhesion performance decreases.

PRODUCT APPLICATION

Securing film packaging around palletized produce which is refrigerated. Recommended application at room temperature to clean, dry surfaces prior to being placed into a reduced temperature environment.

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	Polyester Film
Adhesive	Natural Rubber/Resin
Reinforcement	Fiberglass
Adhesion to Steel (oz/in of width) (at room temperature (70°F/21°C))	19 (5.2 N/25mm)
Tensile Strength (lbs/in of width)	148 (648 N/25mm)
Elongation (at break)	3.5%
Total Thickness (mils)	5.6 (0.142mm)
Quick Stick (oz/in of width)	
To Kraft	3 (0.8 N/25mm)
To Steel	16 (4.4 N/25mm)
Color	Clear



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 07/10

