

T-226

BLASTLITE

INTERTAPE POLYMER GROUP

TECHNICAL DATA SHEET

DESCRIPTION

IPG's answer to Vinyl. Specially formulated rubber provides impact resistance and natural flexibility allowing T226 to conform tightly around curves and uneven surfaces. High-tack acrylic adhesive bonds quickly to clean surfaces. Uniform thickness / high quality / conformable / long-lasting / easy to use. Release treated paper liner permits easy tear by hand. Un-punched / Friction fed. Can also be hand cut by knife for precise fit. Unlike vinyl, T226 does not contain PVC and can be safely cut using laser method.

PRODUCT APPLICATION

Superior surface protection and seal. Especially for use on raw wood, unprimed HDU, brick or unglazed tile.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Adhesive	High Tack Acrylic
Color	Tan
Total Thickness (mil) PSTC-133	28 (0.71 mm)
Tensile Strength (lbs/in) PSTC-131	3 (13 N/25mm)
180° Adhesion to Steel (oz/in) PSTC-101	28 (7.6 N/25mm)
Elongation (% @ break) PSTC-131	450



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 02/11